


Ecoguss drain body glued flange, DN 50, Vertical outlet





Article information

Item no.: 48658

GTIN: 4026092033333

Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The glued flange with a flange width of 50 mm is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes. The loose flange is used for clamping polymer and elastomer sealing sheets as well as for cold bitumen seals and is therefore only suitable for use with moisture barriers.

The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125

Waterproofing layer on the drain body: Adhesive flange (suitable for moisture barriers)

Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1 Nominal size (DN): 50

Outer diameter (OD): 58 mm

Approval: Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-17

19_V

Odour trap: included



Dimensions

Net weight: 1,31 kg
Gross weight: 1,9 kg
Diameter: 348 mm
Height: 205 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets:

Material of drain body: Ecoguss resistant

Socket version: vertical