


Ecoguss drain body glued flange, DN 80, Vertical outlet



Article information

Item no.: 48683
 GTIN: 4026092033371
 Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The glued flange with a flange width of 50 mm is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes. The loose flange is used for clamping polymer and elastomer sealing sheets as well as for cold bitumen seals and is therefore only suitable for use with moisture barriers.

The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125
 Waterproofing layer on the drain body:
 Sealing water height: Adhesive flange (suitable for moisture barriers)
 50 mm

General characteristics

| | |
|----------------------|--|
| Standard: | EN 1253-1 |
| Nominal size (DN): | 80 |
| Outer diameter (OD): | 83 mm |
| Approval: | Z-19.53-2414, Z-19.53-2414_V, Z-19.17-1719, Z-19.17-1719_V |
| Odour trap: | included |

Dimensions

Net weight: 1,33 kg
Gross weight: 1,92 kg
Diameter: 348 mm
Height: 215 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: Ecoguss resistant
Socket version: vertical