


Ecoguss drain body Press. fl., DN 70, Vertical outlet



Article information

Item no.: 48878
 GTIN: 4026092032657
 Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage and a protective cover for the construction period.

The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The glued flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System:

Waterproofing layer on the drain body:

Sealing water height:

125

Press sealing flange (suitable for creating watertight seals)

50 mm

General characteristics

Standard:

EN 1253-1

Nominal size (DN):

70

Outer diameter (OD):

78 mm

Approval:

Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V

Odour trap:

included

Dimensions

Net weight: 2,1 kg

Gross weight: 2,41 kg

Diameter: 273 mm

Height: 217 mm

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

Tank/drain body

Number of outlets: 1

Material of drain body: Ecoguss resistant

Socket version: vertical