


## Linearis Comfort upper section L: 750 mm, System 125, WaD, K 3



### Article information

Item no.: 48928M  
GTIN: 4026092079041  
Price group: 10

### Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

### Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

#### Variant

System:

125

Seepage opening:

open

Waterproofing layer on the upper section:

Factory-fitted sealing collar (WaD) according to DIN 18534

Water exposure class in accordance to DIN

W3-I

18534-1 (up to and including):

50 mm

Sealing water height:

1,1

Discharge rate (l/s) with 10 mm threshold:

1 mm

Discharge rate (l/s) without threshold:

#### General characteristics

Nominal size (DN):

125

Outer diameter (OD):

125 mm

Odour trap:

included

#### Dimensions

Net weight:

3,44 kg

Gross weight:

4,1 kg

Outer dimension, length:

815 mm

Installation depth:

80 - 140 mm

Width:

243 mm

Height:

110 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

**Coverage features**

Type of cover:	Stainless steel cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Frame material:	Stainless steel 14301
Locking:	lockable
Load class:	K 3 (EN 1253-1)
Grating design:	optionally tileable
Rim width:	66 mm
Rim length:	750 mm
Upper section material:	ABS