

# Linearis Comfort upper section L: 1050 mm, System 125, WaD, K 3



## Article information

Item no.: 48931M  
GTIN: 4026092079072  
Price group: 10

## Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

## Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

### Variant

System:

125

Seepage opening:

open

Waterproofing layer on the upper section:

Factory-fitted sealing collar (WaD) according to DIN 18534

Water exposure class in accordance to DIN

W3-I

18534-1 (up to and including):

50 mm

Sealing water height:

1,1

Discharge rate (l/s) with 10 mm threshold:

1 mm

Discharge rate (l/s) without threshold:

### General characteristics

Nominal size (DN):

125

Outer diameter (OD):

125 mm

Odour trap:

included

### Dimensions

Net weight:

4,24 kg

Gross weight:

4,96 kg

Outer dimension, length:

1115 mm

Installation depth:

80 - 140 mm

Width:

243 mm

Height:

115 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

**Coverage features**

|                         |                       |
|-------------------------|-----------------------|
| Type of cover:          | Stainless steel cover |
| Cover material:         | Stainless steel 14301 |
| Colour of cover:        | silver                |
| Surface:                | Brushed SST           |
| Frame material:         | Stainless steel 14301 |
| Locking:                | lockable              |
| Load class:             | K 3 (EN 1253-1)       |
| Grating design:         | optionally tileable   |
| Rim width:              | 66 mm                 |
| Rim length:             | 1050 mm               |
| Shape of upper section: | square                |
| Upper section material: | ABS                   |