

## Ferrofix upper section gl. flange Sys 200, closed cover, 304 SST



### Article information

Item no.: 48954-S-V2A-KF  
 GTIN: 4026092090831  
 Price group: 70

### Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

### Description

Used in combination with a drain body of the KESSEL modular system 200, the Ferrofix stainless steel upper section with glued flange is suitable for indoor point drainage.

#### Variant

System:	200
Waterproofing layer on the upper section:	Adhesive flange (suitable for moisture barriers)
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I

#### Dimensions

Net weight:	4 kg
Gross weight:	4,3 kg
Type of height adjustability:	vertically adjustable upper section
Length:	300 mm
Height:	110 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Coverage features

Type of cover:	closed cover plate with drain slots
Cover material:	Stainless steel 14301
Height of cover:	15 mm
Surface:	Polished SST
Locking:	screwed
Load class:	L 15 (EN 1253-1)
Rim width:	200 mm
Rim length:	200 mm
Shape of upper section:	square

Upper section material:

Stainless steel 14301