


## Variofix upper section System 200, slot grat., 304 SST, L 15





## **Article information**

Item no.: 48969

GTIN: 4026092005132

Price group: 70

## **Advantages**

- Different covers selectable
- Including waterproofing membrane

## **Description**

Used in combination with a drain body of the KESSEL modular system, the upper section is suitable for indoor point drainage.

Variant

System: 200

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water exposure class in accordance to DIN

18534-1 (up to and including):

W3-I

General characteristics

Sustainable: through the use of recycled material

**Dimensions** 

Vertical adjustment:30 - 50 mmNet weight:2,99 kgGross weight:3,72 kgDiameter:320 mm

Type of height adjustability: vertically adjustable upper section

Height: 150 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Coverage features



Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver
Height of cover: 28 mm
Min. flooring height: 30 mm
Surface: pickled
Locking: placed

Load class: L 15 (EN 1253-1)

Grating design: Cross
Rim width: 200 mm
Rim length: 200 mm
Max. flooring height: 50 mm

Upper section: adjustable in three dimensions

Shape of upper section: square Upper section material: ABS

Mesh size: 23 x 23 mm