


## Ferrofix drain body, glued flange Sys 125, DN 70, horizontal outlet



### Article information

Item no.: 54300  
 GTIN: 4026092072349  
 Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- Variably combinable with upper sections

### Description

In combination with a System 125 upper section, the Ferrofix stainless steel drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The glued flange with a flange width of 50 mm is suitable for joint sealings in accordance with DIN 18534, for all waterproofing classes. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

#### Variant

System:	125
Waterproofing layer on the drain body:	Adhesive flange (suitable for moisture barriers)
Sealing water height:	50 mm

#### General characteristics

Standard:	EN 1253-1
Nominal size (DN):	70
Outer diameter (OD):	78 mm
Odour trap:	included

#### Dimensions

Net weight:	1,3 kg
Gross weight:	1,58 kg
Length:	240 mm
Width:	240 mm
Height:	147 mm
Packaging dimension:	length

Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	Stainless steel 14301
Socket version:	lateral