


## Ferrofix floor/roof drain DN 70, horizontal, Slotted grating



### Article information

Item no.: 54400.61  
 GTIN: 4026092056523  
 Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- High flow rate

### Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap made of stainless steel, a lip seal and a temporary protective cover. The outlet socket is suitable for connection to SML cast iron pipes.

#### Variant

|                                           |                   |
|-------------------------------------------|-------------------|
| System:                                   | 125               |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body:    | Connection flange |
| Sealing water height:                     | 50 mm             |

#### General characteristics

|                      |           |
|----------------------|-----------|
| Standard:            | EN 1253-1 |
| Nominal size (DN):   | 70        |
| Outer diameter (OD): | 78 mm     |
| Odour trap:          | included  |

#### Dimensions

|                               |                                     |
|-------------------------------|-------------------------------------|
| Net weight:                   | 2,04 kg                             |
| Gross weight:                 | 2,41 kg                             |
| Type of height adjustability: | vertically adjustable upper section |
| Length:                       | 181 mm                              |
| Width:                        | 142 mm                              |
| Packaging dimension:          | length                              |
| Packaging dimension:          | width                               |

|                         |                                                      |
|-------------------------|------------------------------------------------------|
| Packaging dimension:    | height                                               |
| Tank/drain body         |                                                      |
| Number of outlets:      | 1                                                    |
| Material of drain body: | Stainless steel 14301                                |
| Socket version:         | lateral                                              |
| Coverage features       |                                                      |
| Type of cover:          | Slotted cover                                        |
| Cover material:         | Stainless steel 14301                                |
| Width of cover:         | 138 mm                                               |
| Length of cover:        | 138 mm                                               |
| Locking:                | screwed                                              |
| Load class:             | L 15 (EN 1253-1)                                     |
| Slip resistance class:  | R11 according to DIN 51130; C according to DIN 51097 |
| Rim width:              | 150 mm                                               |
| Rim length:             | 150 mm                                               |
| Upper section:          | vertically adjustable                                |
| Upper section material: | ABS                                                  |