



Drain body Ferrofix Press. fl. DN100,hori.,with OT and sludge bucket



Article information

Item no.: 55115
GTIN: 4026092107522
Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- Variably combinable with upper sections

Description

In combination with a System 185 upper section, the Ferrofix stainless steel drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only membranes tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. With a drainage capacity ■ 2.4 l/s with 20 mm build-up.

Variant	
System:	185
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
Sealing water height:	50 mm
General characteristics	
Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	201 mm
Odour trap:	included
Dimensions	
Net weight:	2 kg
Gross weight:	3 kg
Width:	404 mm

Height:	180 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	Stainless steel 14301
Socket version:	lateral