

Ferrofix upper section Sys 125, Gl fl., Slot cover, 100x100 mm



Article information

Item no.: 59165
 GTIN: 4026092103593
 Price group: 70

Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

Description

Used in combination with a drain body of the KESSEL modular system 125, the stainless steel upper section is suitable for indoor point drainage. The upper section is suitable for thin-layered floorings (e.g. epoxy resin) and has a circumferential adhesive joint edge (15 mm deep and 50 mm folded outwards).

| | |
|---|--|
| Variant | |
| System: | 125 |
| Waterproofing layer on the upper section: | Adhesive flange (suitable for moisture barriers) |

| | |
|----------------------|--------|
| Dimensions | |
| Net weight: | 2 kg |
| Gross weight: | 2,2 kg |
| Length: | 200 mm |
| Width: | 200 mm |
| Height: | 90 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

| | |
|-------------------------|-----------------------|
| Coverage features | |
| Type of cover: | Slotted cover |
| Cover material: | Stainless steel 14301 |
| Height of cover: | 15 mm |
| Locking: | unlocked |
| Load class: | K 3 (EN 1253-1) |
| Rim width: | 100 mm |
| Rim length: | 100 mm |
| Max. flooring height: | 20 mm |
| Shape of upper section: | square |
| Upper section material: | Stainless steel 14301 |