


Ferrofix renovation drain DN 50, horizontal, Slotted grating, L 15



Article information

Item no.: 59305
 GTIN: 4026092103012
 Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- ideal for the food industry
- catering kitchens and swimming pools

Description

The Ferrofix stainless steel renovation drain is equipped with a horizontal outlet DN 50 as well as a removable odour trap.

Variant

| | |
|--|-------------------|
| System: | 125 |
| Waterproofing layer on the upper section: | Connection flange |
| Sealing water height: | 50 mm |
| Discharge rate (l/s) with 20 mm threshold: | 0,8 |

General characteristics

| | |
|----------------------|----------|
| Nominal size (DN): | 50 |
| Outer diameter (OD): | 50 mm |
| Odour trap: | included |

Dimensions

| | |
|----------------------|--------|
| Net weight: | 1 kg |
| Gross weight: | 3,1 kg |
| Max. design height: | 107 mm |
| Length: | 223 mm |
| Width: | 148 mm |
| Height: | 107 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

| | |
|-------------------------|-----------------------|
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | Stainless steel 14301 |
| Socket version: | lateral |
| Coverage features | |
| Type of cover: | Slotted cover |
| Cover material: | Stainless steel 14301 |
| Width of cover: | 138 mm |
| Length of cover: | 138 mm |
| Locking: | unlocked |
| Load class: | L 15 (EN 1253-1) |
| Rim width: | 148 mm |
| Rim length: | 148 mm |
| Upper section material: | Stainless steel 14301 |