


## Ferrofix renovation drain DN 50, horizontal, Slotted grating, L 15



### Article information

Item no.: 59305  
 GTIN: 4026092103012  
 Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- ideal for the food industry
- catering kitchens and swimming pools

### Description

The Ferrofix stainless steel renovation drain is equipped with a horizontal outlet DN 50 as well as a removable odour trap.

#### Variant

System:	125
Waterproofing layer on the upper section:	Connection flange
Sealing water height:	50 mm
Discharge rate (l/s) with 20 mm threshold:	0,8

#### General characteristics

Nominal size (DN):	50
Outer diameter (OD):	50 mm
Odour trap:	included

#### Dimensions

Net weight:	1 kg
Gross weight:	3,1 kg
Max. design height:	107 mm
Length:	223 mm
Width:	148 mm
Height:	107 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body	
Number of outlets:	1
Material of drain body:	Stainless steel 14301
Socket version:	lateral

#### Coverage features

Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Width of cover:	138 mm
Length of cover:	138 mm
Locking:	unlocked
Load class:	L 15 (EN 1253-1)
Rim width:	148 mm
Rim length:	148 mm
Upper section material:	Stainless steel 14301