


Slotted Channel Ferrofix glued flange H: 15mm, 17x2000mm, middle





Article information

Item no.: 6002200 GTIN: 4026092099520

Price group: 80

Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

Description

The Ferrofix slotted channel made of stainless steel with a material thickness of 2.0 mm (pickled in the immersion bath) is equipped with polished visible ridges, longitudinal and transverse slopes, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for joint sealing and has a circumferential adhesive edge (15 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes.

Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)

Water exposure class in accordance to DIN W3-I

18534-1 (up to and including):

Position of sink trap: central

General characteristics

Material: Stainless steel 14301

Nominal size (DN): 125 Outer diameter (OD): 125 mm Glued flange height: 15 mm

Dimensions

Length:2000 mmWidth:17 mmHeight:75 mm



Coverage features

Type of cover: Slotted cover

Colour of cover:silverWidth of cover:200 mmLength of cover:200 mmLocking:placed

Load class: L 15 (EN 1253-1)

Slip resistance class: R12 according to DIN 51130; C according to DIN

51097

Slot width: 17 mm