


# Box channel Ferrofix glued flange H: 15mm, 300x2050mm





#### **Article information**

Item no.: 6030200 GTIN: 4026092054697

Price group: 80

### **Advantages**

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

## **Description**

The Ferrofix box channel made of stainless steel with a material thickness of 2.0 mm (pickled in the immersion bath) is equipped with polished visible ridges, longitudinal and transverse slopes, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for joint sealing and has a circumferential adhesive edge (15 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes.

#### Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)

Water exposure class in accordance to DIN W3-I

18534-1 (up to and including):

General characteristics

Nominal size (DN): 125
Outer diameter (OD): 125 mm
Glued flange height: 15 mm

**Dimensions** 

Net weight:31 kgGross weight:31 kgLength:2050 mmWidth:300 mmHeight:60 mmPackaging dimension:length



Packaging dimension: width Packaging dimension: height

Coverage features

Type of cover: Slotted cover

Colour of cover: silver Locking: placed

Load class: L 15 (EN 1253-1)

Slip resistance class: R12 according to DIN 51130; C according to DIN

51097

Upper section material: Stainless steel 14301