


Box channel Ferrofix glued flange H: 15mm, 400x2050mm





Article information

Item no.: 6040200 GTIN: 4026092098691

Price group: 80

Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

Description

The Ferrofix box channel made of stainless steel with a material thickness of 2.0 mm (pickled in the immersion bath) is equipped with polished visible ridges, longitudinal and transverse slopes, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for joint sealing and has a circumferential adhesive edge (15 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes.

Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers) W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

General characteristics

Nominal size (DN): 125 Outer diameter (OD): 125 mm Glued flange height: 15 mm

Dimensions

2050 mm Length: Width: 400 mm Height: 60 mm

Coverage features

Type of cover: Slotted cover



Colour of cover: silver Locking: placed

Load class: L 15 (EN 1253-1)

Slip resistance class: R12 according to DIN 51130; C according to DIN

51097

Upper section material: Stainless steel 14301