


Floor Tray Ferrofix glued flange H: 15mm, 600x600mm





Article information

Item no.: 6060600 GTIN: 4026092099308

Price group: 80

Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

Description

The Ferrofix floor tray made of stainless steel with a material thickness of 2.0 mm (pickled in the immersion bath) is equipped with polished visible ridges, longitudinal and transverse slopes, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for joint sealing and has a circumferential adhesive edge (15 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes.

Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)

Water exposure class in accordance to DIN W3-I

18534-1 (up to and including):

General characteristics

Nominal size (DN): 125 Outer diameter (OD): 125 mm Glued flange height: 15 mm

Dimensions

Net weight: 19,4 kg
Gross weight: 19,4 kg
Length: 600 mm
Width: 600 mm
Height: 60 mm
Packaging dimension: length



Packaging dimension: width Packaging dimension: height

Coverage features

Type of cover: Slotted cover

Colour of cover: silver Locking: placed

Load class: L 15 (EN 1253-1)

Slip resistance class: R12 according to DIN 51130; C according to DIN

51097

Upper section material: Stainless steel 14301