



## Slotted Channel Ferrofix without glued flange, 17x1000mm, outer



### Article information

Item no.: 6102101  
 GTIN: 4026092099698  
 Price group: 80

### Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

### Description

The Slotted Channel Ferrofix made of stainless steel with a material thickness of 2.0 mm (pickled in the immersion bath) is equipped with polished visible ridges, longitudinal and transverse slopes, feet for height adjustment and stainless steel outlet nozzles.

#### Variant

Waterproofing layer on the upper section:  
 Position of sink trap:

Connection flange  
 outside

#### General characteristics

Material:  
 Nominal size (DN):  
 Outer diameter (OD):

Stainless steel 14301  
 125  
 125 mm

#### Dimensions

Length:  
 Width:  
 Height:

1000 mm  
 17 mm  
 75 mm

#### Coverage features

Type of cover:  
 Colour of cover:  
 Width of cover:  
 Length of cover:  
 Locking:

Slotted cover  
 silver  
 200 mm  
 200 mm  
 placed

Load class:	L 15 (EN 1253-1)
Slip resistance class:	R12 according to DIN 51130; C according to DIN 51097
Slot width:	17 mm