


Slotted Channel Ferrofix glued flange H: 6mm, 17x1400mm, outer





Article information

Item no.: 6202141 GTIN: 4026092099612

Price group: 80

Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

Description

The Ferrofix slotted channel made of stainless steel with a material thickness of 1.5 mm (pickled in the immersion bath) is equipped with ground crosspieces, longitudinal and transverse gradients, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for thin-layered floorings (e.g. epoxy resin) and has an all-round adhesive rim (6 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is also suitable for connecting waterproofing.

Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)

Position of sink trap: outside

General characteristics

Material: Stainless steel 14301

Nominal size (DN): 125 Outer diameter (OD): 125 mm Glued flange height: 6 mm

Dimensions

Length: 1400 mm Width: 17 mm Height: 75 mm

Coverage features

Type of cover: Slotted cover



Colour of cover:silverWidth of cover:200 mmLength of cover:200 mmLocking:placed

Load class: L 15 (EN 1253-1)

Slip resistance class: R12 according to DIN 51130; C according to DIN

51097

Slot width: 17 mm