


## Floor Tray Ferrofix glued flange H: 6mm, 800x800mm





## **Article information**

Item no.: 6280800 GTIN: 4026092099353

Price group: 80

## **Advantages**

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

## **Description**

The Ferrofix floor tray made of stainless steel with a material thickness of 1.5 mm (pickled in the immersion bath) is equipped with ground crosspieces, longitudinal and transverse gradients, feet for height adjustment and stainless steel outlet nozzles The channel profile is suitable for thin-layered floorings (e.g. epoxy resin) and has an all-round adhesive rim (6 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is also suitable for connecting waterproofing.

Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)

General characteristics

Nominal size (DN): 125 Outer diameter (OD): 125 mm Glued flange height: 6 mm

Dimensions

Length:800 mmWidth:800 mmHeight:60 mm

Coverage features

Type of cover: Slotted cover

Colour of cover: silver Locking: placed

Load class: L 15 (EN 1253-1)



Slip resistance class:

R12 according to DIN 51130; C according to DIN 51097 Stainless steel 14301

Upper section material: