

Yard drain System 100, vert., slot grat., B 125



Article information

Item no.: 67110B
GTIN: 4026092039373
Price group: 10

Advantages

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Variant

System: 100
Contents of sludge trap: yes

General characteristics

Nominal size (DN): 100
Odour trap: no

Dimensions

Net weight: 2,9 kg
Gross weight: 2,9 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: Ecoguss Heavy Duty
Socket version: vertical

Coverage features

Type of cover: Round slotted cover
Cover material: Ecoguss
Colour of cover: black

Width of cover:	247 mm
Length of cover:	247 mm
Surface:	EDM
Locking:	Lock & Lift
Load class:	B 125 (EN 124)
Shape of upper section:	square
Contents of sludge trap:	yes