


## Upper section with slotted cover d: 218 mm, A/L15



### Article information

Item no.: 67986  
 GTIN: 4026092085493  
 Price group: 10

### Advantages

- Multiple combinations with suitable drain bodies

### Description

The polymer upper section is suitable for LW 400 chamber systems and is equipped with a clamping ring and a hanger for sludge buckets. Continuously height-adjustable by 440 mm. If installed in roads, parking areas and comparable hard-surfaced traffic areas for trucks (Class D), the upper section must be underlaid on site with an approx. 15 cm thick reinforced supporting slab with at least 0.80 x 0.80 m made of B35 concrete. The exact design of the concrete slab must be calculated structurally according to the circumstances on site. A standard formwork and reinforcement drawing can be provided.

#### Variant

System: 200

#### Dimensions

Net weight:	4,4 kg
Gross weight:	4,9 kg
Diameter:	218 mm
Type of height adjustability:	vertically adjustable upper section
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Coverage features

Cover material:	Polymer
Colour of cover:	black
Load class:	A 15 (EN 124) / L 15 (EN 1253-1)

Rim width: 300 mm  
Rim length: 300 mm  
Upper section material: Polymer