

Replacement pump, Pumpfix F DN 150, 5 m cable



Article information

Item no.: 680039
 GTIN: 4026092062326
 Price group: 90

Description

Replacement pump with cover, motor, impeller, blades and pump housing for faecal wastewater

Variant

Pump control: Control unit

General characteristics

Standard: EN 12050-1
 Type of wastewater: with sewage

Dimensions

Net weight: 13,92 kg
 Gross weight: 15,45 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: SPZ 1000
 Connection type: Schuko (earthed contact) 2-pin
 Operating voltage: 230 V
 Mains frequency: 50 Hz
 Protection class: I
 Insulation class: F
 Cos phi - power factor: 0,97
 Protection class (pump): IP 68 (3m/48h)
 Temperature monitoring: integrated
 Max. temperature (permanent) of conveyed material: 35 °C
 Max. pumping height: 10 m
 Speed: 2800 U/min
 Power P1: 1,2 kW
 Power P2: 0,7 kW

| | |
|---------------------------------|--------------------------------|
| Operating mode: | S3 - 30 % |
| Type of pump connection cable: | H07RN-F 3G 1.5 mm ² |
| Impeller type: | Macerator |
| Type of fuse required (pump): | C 16 A |
| Length of mains cable for pump: | 5 m |
| Rated current: | 5,2 A |
| Control | |
| Operating voltage: | 230 V |
| Connection type: | Schuko (earthed contact) 2-pin |