

## Replacement pump pumping station dry installation SPF 4500-S1



### Article information

Item no.: 680534  
GTIN: 4026092074954  
Price group: 90

### Description

Replacement pump type SPF 4500-S1 for Aqualift FXL pumping station, dry installation

#### Variant

Pump control: Control unit

#### General characteristics

Cable length: 10 m

#### Dimensions

Net weight: 33,2 kg  
Gross weight: 36 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Pump: SPF 4500-S1  
Connection type: Direct connection  
Operating voltage: 400 V  
Mains frequency: 50 Hz  
Protection class: I  
Insulation class: F  
Cos phi - power factor: 0,85  
Protection class (pump): IP 68  
Max. temperature (permanent) of conveyed material: 40 °C  
Max. pumping height: 20 m  
Speed: 2850 U/min  
Power P1: 4,2 kW  
Power P2: 3,5 kW  
Operating mode: S3 - 50 %  
Type of pump connection cable: H07RN-F 7G 1.5 mm<sup>2</sup>

Type of fuse required (pump): Fuse protection through control unit 400 V  
Length of mains cable for pump: 10 m  
Rated current: 7,5 A

Control

Operating voltage: 400 V  
Connection type: Direct connection