

Replacem. pump Aquadive STZ 1300 without float switch, 10 m, ATEX



Article information

Item no.: 680604
GTIN: 4026092078488
Price group: 90

Description

Replacement pump, Aquadive STZ 1300, ATEX, without float, for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight: 27 kg
Gross weight: 30 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: STZ 1300
Weight, pump: 27 kg
Connection type: Direct connection
Operating voltage: 400 V
Mains frequency: 50 Hz
Protection class: I
Insulation class: H
Cos phi - power factor: 0,8
Protection class (pump): IP 68
Max. temperature (permanent) of conveyed material: 40 °C
Max. pumping height: 21 m
Speed: 2900 U/min
Power P1: 1,3 kW

Power P2:	0,9 kW
Operating mode:	S1
Type of pump connection cable:	H07RN8-F 6G 1.5 mm ²
Impeller type:	Macerator
Type of fuse required (pump):	Fuse protection through control unit 400 V
Length of mains cable for pump:	10 m
Rated current:	2,5 A
Control	
Operating voltage:	400 V
Connection type:	Direct connection