

Replacem. pump Aquadive STZ 2500 without float switch, 10 m, ATEX



Article information

Item no.: 680605 GTIN: 4026092078495

Price group: 90

Description

Replacement pump, Aquadive, STZ 2500, ATEX, without float, for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight:37 kgGross weight:39 kgPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Pumping device

Pump: STZ 2500 Weight, pump: 33 kg

Connection type: Direct connection

Operating voltage: 400 V
Mains frequency: 50 Hz
Protection class: I
Insulation class: H
Cos phi - power factor: 0,83
Protection class (pump): IP 68
Max. temperature (permanent) of conveyed 40 °C

material:

Max. pumping height: 33 m

 Speed:
 2900 U/min

 Power P1:
 2,5 kW



Power P2: 1,9 kW Operating mode: S1

Type of pump connection cable: H07RN8-F 6G 1.5 mm²

Impeller type: Macerator

Type of fuse required (pump): Fuse protection through control unit 400 V

Length of mains cable for pump: 10 m Rated current: 4,4 A

Control

Operating voltage: 400 V

Connection type: Direct connection