

Replacem. pump Aquadive STZ 3700 without float switch, 10 m, ATEX



Article information

Item no.: 680606
GTIN: 4026092078501
Price group: 90

Description

Replacement pump, Aquadive, STZ 3700, ATEX, without floater, for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight:	43 kg
Gross weight:	46 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Pumping device

Pump:	STZ 3700
Weight, pump:	44 kg
Connection type:	Direct connection
Operating voltage:	400 V
Mains frequency:	50 Hz
Protection class:	I
Insulation class:	H
Cos phi - power factor:	0,82
Protection class (pump):	IP 68
Temperature monitoring:	controlled via control unit
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping height:	35 m
Speed:	2900 U/min

Power P1:	3,7 kW
Power P2:	3,1 kW
Operating mode:	S1
Type of pump connection cable:	H07RN8-F 6G 1.5 mm ²
Impeller type:	Macerator
Type of fuse required (pump):	Fuse protection through control unit 400 V
Length of mains cable for pump:	10 m
Rated current:	6,4 A
Control	
Operating voltage:	400 V
Connection type:	Direct connection