

Replacem. pump Aquadive STZ 3700 without float switch, 10 m, ATEX



Article information

Item no.: 680606 GTIN: 4026092078501 Price group: 90

Description

Replacement pump, Aquadive, STZ 3700, ATEX, without floater, for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight:43 kgGross weight:46 kgPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Pumping device

Pump: STZ 3700 Weight, pump: 44 kg

Connection type: Direct connection

Operating voltage: 400 V
Mains frequency: 50 Hz
Protection class: I
Insulation class: H
Cos phi - power factor: 0,82
Protection class (pump): IP 68

Temperature monitoring: controlled via control unit

Max. temperature (permanent) of conveyed 40 °C

material:

Max. pumping height: 35 m

Speed: 2900 U/min



Power P1: 3,7 kW
Power P2: 3,1 kW
Operating mode: S1

Type of pump connection cable: H07RN8-F 6G 1.5 mm²

Impeller type: Macerator

Type of fuse required (pump): Fuse protection through control unit 400 V

Length of mains cable for pump: 10 m Rated current: 6,4 A

Control

Operating voltage: 400 V

Connection type: Direct connection