

Replacement pump STZ 4400 without float switch, ATEX



Article information

Item no.: 680703
GTIN: 4026092081983
Price group: 90

Description

Replacement pump without float switch for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Type of wastewater: for wastewater with and without sewage

Dimensions

Net weight:	55 kg
Gross weight:	57 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Pumping device

Pump:	STZ 4400
Weight, pump:	56 kg
Connection type:	Direct connection
Operating voltage:	400 V
Mains frequency:	50 Hz
Protection class:	I
Insulation class:	H
Cos phi - power factor:	0,89
Protection class (pump):	IP 68
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping height:	46,7 m
Speed:	2840 U/min
Power P1:	4,4 kW
Power P2:	3,7 kW
Operating mode:	S1

Type of pump connection cable:	H07RN8-F PLU 7G 1.5 mm ²
Impeller type:	Macerator
Type of fuse required (pump):	Fuse protection through control unit 400 V
Length of mains cable for pump:	10 m
Rated current:	7,5 A
Control	
Operating voltage:	400 V
Connection type:	Direct connection