

## Replacement pump STZ 4400 without float switch, ATEX



## **Article information**

Item no.: 680703 GTIN: 4026092081983

Price group: 90

## **Description**

Replacement pump without float switch for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Type of wastewater: for wastewater with and without sewage

**Dimensions** 

Net weight: 55 kg Gross weight: 57 kg Packaging dimension: length Packaging dimension: width Packaging dimension: height

Pumping device

Pump: STZ 4400 Weight, pump: 56 kg

Connection type: Direct connection

Operating voltage: 400 V Mains frequency: 50 Hz Protection class: Insulation class: Н Cos phi - power factor: 0,89 IP 68 Protection class (pump): Temperature monitoring: integrated 40 °C

Max. temperature (permanent) of conveyed

material:

Max. pumping height: 46.7 m Speed: 2840 U/min Power P1: 4,4 kW Power P2: 3,7 kW Operating mode: S1



Type of pump connection cable: H07RN8-F PLU 7G 1.5 mm<sup>2</sup>

Impeller type: Macerator

Type of fuse required (pump): Fuse protection through control unit 400 V

Length of mains cable for pump: 10 m Rated current: 7,5 A

Control

Operating voltage: 400 V

Connection type: Direct connection