

## Replacement pump STZ 5200 without float switch, ATEX



### Article information

Item no.: 680704  
 GTIN: 4026092081990  
 Price group: 90

### Description

Replacement pump without float switch for pumping station, wet installation

#### Variant

Pump control: Control unit

#### General characteristics

Type of wastewater: for wastewater with and without sewage

#### Dimensions

Net weight: 58 kg  
 Gross weight: 60 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: STZ 5200  
 Weight, pump: 56 kg  
 Connection type: Direct connection  
 Operating voltage: 400 V  
 Mains frequency: 50 Hz  
 Protection class: I  
 Insulation class: H  
 Cos phi - power factor: 0,89  
 Protection class (pump): IP 68  
 Temperature monitoring: integrated  
 Max. temperature (permanent) of conveyed material: 40 °C  
 Max. pumping height: 52 m  
 Speed: 2840 U/min  
 Power P1: 5,2 kW  
 Power P2: 4,4 kW  
 Operating mode: S1

Type of pump connection cable:	H07RN8-F PLU 10G 1.5 mm <sup>2</sup>
Impeller type:	Macerator
Type of fuse required (pump):	Fuse protection through control unit 400 V
Length of mains cable for pump:	10 m
Rated current:	8,7 A
Control	
Operating voltage:	400 V
Connection type:	Direct connection