

## Replacement pump GTK 5200 without float switch



### Article information

Item no.: 680708  
 GTIN: 4026092082034  
 Price group: 90

### Description

Replacement pump GTK 5200 without float switch, for pumping station, wet installation

#### Variant

Pump control: Control unit

#### General characteristics

Type of wastewater: without sewage

#### Dimensions

Net weight: 57 kg  
 Gross weight: 59 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: GTK 5200  
 Weight, pump: 56 kg  
 Connection type: Direct connection  
 Operating voltage: 400 V  
 Mains frequency: 50 Hz  
 Protection class: I  
 Insulation class: H  
 Cos phi - power factor: 0,85  
 Protection class (pump): IP 68  
 Max. temperature (permanent) of conveyed material: 40 °C  
 Max. pumping height: 31,6 m  
 Speed: 2840 U/min  
 Power P1: 5,2 kW  
 Power P2: 4,4 kW  
 Operating mode: S3 - 30 %

|                                 |  |
|---------------------------------|--|
| Type of pump connection cable:  | H07RN8-F PLU 10G 1.5 mm <sup>2</sup>       |
| Type of fuse required (pump):   | Fuse protection through control unit 400 V |
| Length of mains cable for pump: | 10 m                                       |
| Rated current:                  | 8,7 A                                      |
| Control                         |  |
| Operating voltage:              | 400 V                                      |
| Connection type:                | Direct connection                          |