

## Replacement pump GTF 600 with float switch, 10 m



### Article information

Item no.: 680963  
 GTIN: 4026092095386  
 Price group: 90

### Description

Replacement pump with float switch for wastewater containing faecal matter.

Variant	
Pump control:	Float switch
General characteristics	
Type of wastewater:	without sewage
Dimensions	
Net weight:	6,85 kg
Gross weight:	6,85 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	GTF 600
Connection type:	Schuko (earthed contact) 2-pin
Operating voltage:	230 V
Mains frequency:	50 Hz
Protection class (pump):	IP 68 (3m)
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping height:	8 m
Speed:	2750 U/min
Power P1:	0,65 kW
Power P2:	0,4 kW
Operating mode:	S1
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	2,9 A

Control

Operating voltage:

230 V

Connection type:

Schuko (earthed contact) 2-pin