

Replacement pump GTF 1250 w. float switch, Aqualift S 100/200, 5m



Article information

Item no.: 680978
GTIN: 4026092095911
Price group: 90

Description

Replacement pump with float switch for faecal-free wastewater.

Variant

Pump control: **Float switch**

General characteristics

Type of wastewater: **without sewage**

Dimensions

Net weight: **10,5 kg**

Gross weight: **10,5 kg**

Packaging dimension: **length**

Packaging dimension: **width**

Packaging dimension: **height**

Pumping device

Pump: **GTF 1250**

Connection type: **Schuko (earthed contact) 2-pin**

Operating voltage: **230 V**

Mains frequency: **50 Hz**

Protection class (pump): **IP 68 (3m)**

Max. temperature (permanent) of conveyed material: **40 °C**

Max. pumping height: **11 m**

Speed: **2700 U/min**

Power P1: **1,3 kW**

Power P2: **0,8 kW**

Operating mode: **S3 - 50 %**

Type of pump connection cable: **H07RN-F 3G 1.5 mm²**

Impeller type: **Multi-vane impeller**

Type of fuse required (pump): **C 16 A**

Length of mains cable for pump: 5 m
Rated current: 5,4 A

Control
Operating voltage: 230 V
Connection type: Schuko (earthed contact) 2-pin