
KESSEL

Staufix clean out DN 90, Floor slab, tileable





Article information

Item no.: 700090.10X GTIN: 4026092075876 Price group: 10

Advantages

- Simple conversion to Staufix type 1
- Own gradient only 8 mm
- Quick and toolless access for cleaning

Description

The clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work. Thanks to the modular KESSEL system, existing systems can easily be supplemented by up to two flaps and one emergency closure or be converted to the StaufixControl backwater valve.

General characteristics Colour: Nominal size (DN): Outer diameter (OD): Type of wastewater: Installation situation: Delivery state:	black 90 90 mm for wastewater with and without sewage floor slab installation Installation-ready (connection parts must be connected on site)
Dimensions	
Net weight:	5,8 kg
Gross weight:	8,4 kg
Groundwater resistant from lower edge of base section:	3 mm
Cutout dimension, width:	750 mm
Cutout dimension, length:	750 mm
Vertical drop between inlet and outlet:	8 mm
Installation depth:	287 - 410 mm
Type of height adjustability:	vertically adjustable upper section



Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Coverage features Type of cover: Cover material: Width of cover: Length of cover: Locking: Load class: Tightness: Max. flooring height: 444 mm 444 mm length width height

tileable cover plate Polymer 366 mm 366 mm Lock & Lift K 3 (EN 1253-1) surface water resistant 18 mm