

## Backwater valve Staufix DN 125, exposed, Type 1



## **Article information**

Item no.: 720125

GTIN: 4026092076057

Price group: 10

## **Advantages**

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

## **Description**

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

Variant

Emergency closure: yes Mechanical backwater flaps: 1

General characteristics

Colour: black
Standard: EN 13564
Nominal size (DN): 125

Outer diameter (OD): 125 mm

Type of wastewater: without sewage Installation situation: exposed drainage pipe

Installation situation: exposed drainage pip Delivery state: installation-ready

Backwater protection: Type 1

**Dimensions** 

Net weight: 3,1 kg 5,7 kg Gross weight: Vertical drop between inlet and outlet: 8 mm Length: 511 mm Width: 216 mm Height: 306 mm Packaging dimension: length Packaging dimension: width



Packaging dimension: height

Coverage features

Type of cover:

Cover locking:

Lockable cover

One-handed closure