


Backwater valve Staufix DN 90, exposed, Type 2 R



Article information

Item no.: 730090R
 GTIN: 4026092076347
 Price group: 10

Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant

Stainless steel flap as rat protection: yes
 Emergency closure: yes
 Mechanical backwater flaps: 2

General characteristics

Colour: black
 Standard: EN 13564
 Nominal size (DN): 90
 Outer diameter (OD): 90 mm
 Type of wastewater: without sewage
 Installation situation: exposed drainage pipe
 Delivery state: installation-ready
 Backwater protection: Type 2

Dimensions

Net weight: 1,4 kg
 Gross weight: 4 kg

Vertical drop between inlet and outlet: 8 mm
Length: 385 mm
Width: 167 mm
Height: 230 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Coverage features

Type of cover: Lockable cover
Cover locking: One-handed closure