

## Backwater valve Staufix DN 100, exposed, Type 2 R



### Article information

Item no.: 730100R  
 GTIN: 4026092076408  
 Price group: 10

### Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

### Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

#### Variant

|   |     |
|---|-----|
| Stainless steel flap as rat protection: | yes |
| Emergency closure:                      | yes |
| Mechanical backwater flaps:             | 2   |

#### General characteristics

|                         |                       |
|-------------------------|-----------------------|
| Colour:                 | black                 |
| Standard:               | EN 13564              |
| Nominal size (DN):      | 100                   |
| Outer diameter (OD):    | 110 mm                |
| Type of wastewater:     | without sewage        |
| Installation situation: | exposed drainage pipe |
| Delivery state:         | installation-ready    |
| Backwater protection:   | Type 2                |

#### Dimensions

|   |        |
|---|--------|
| Net weight:                             | 1,4 kg |
| Gross weight:                           | 4 kg   |
| Vertical drop between inlet and outlet: | 8 mm   |
| Length:                                 | 389 mm |
| Width:                                  | 167 mm |
| Height:                                 | 230 mm |
| Packaging dimension:                    | length |
| Packaging dimension:                    | width  |

Packaging dimension:

height

Coverage features

Type of cover:

Lockable cover

Cover locking:

One-handed closure