


Backwater valve Staufix DN 125, exposed, Type 2



Article information

Item no.: 730125
 GTIN: 4026092076415
 Price group: 10

Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant

Stainless steel flap as rat protection: no
 Emergency closure: yes
 Mechanical backwater flaps: 2

General characteristics

Colour: black
 Standard: EN 13564
 Nominal size (DN): 125
 Outer diameter (OD): 125 mm
 Type of wastewater: without sewage
 Installation situation: exposed drainage pipe
 Delivery state: installation-ready
 Backwater protection: Type 2

Dimensions

Net weight: 3,26 kg
 Gross weight: 3,94 kg

Vertical drop between inlet and outlet: 8 mm
Length: 511 mm
Width: 216 mm
Height: 306 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Coverage features

Type of cover: Lockable cover
Cover locking: One-handed closure