

## Backwater valve Staufix DN 125, exposed, Type 2 R



## **Article information**

Item no.: 730125R GTIN: 4026092076460

Price group: 10

## **Advantages**

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

## **Description**

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant

Stainless steel flap as rat protection: yes
Emergency closure: yes
Mechanical backwater flaps: 2

General characteristics

Colour: black
Standard: EN 13564
Nominal size (DN): 125
Outer diameter (OD): 125 mm

Type of wastewater: without sewage

Installation situation: exposed drainage pipe
Delivery state: installation-ready

Backwater protection: Type 2

**Dimensions** 

Net weight: 3.2 kg5,8 kg Gross weight: Vertical drop between inlet and outlet: 8 mm Length: 515 mm Width: 214 mm Height: 306 mm Packaging dimension: length Packaging dimension: width



Packaging dimension: height

Coverage features

Type of cover:

Cover locking:

Lockable cover

One-handed closure