

## Backwater valve Staufix DN 150, exposed, Type 2 R



### Article information

Item no.: 730150R  
GTIN: 4026092076521  
Price group: 10

### Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

### Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

#### Variant

Stainless steel flap as rat protection: yes  
Emergency closure: yes  
Mechanical backwater flaps: 2

#### General characteristics

Colour: black  
Standard: EN 13564  
Nominal size (DN): 150  
Outer diameter (OD): 160 mm  
Type of wastewater: without sewage  
Installation situation: exposed drainage pipe  
Delivery state: installation-ready  
Backwater protection: Type 2

#### Dimensions

Net weight: 3,32 kg  
Gross weight: 5,9 kg  
Vertical drop between inlet and outlet: 8 mm  
Length: 523 mm  
Width: 216 mm  
Height: 306 mm  
Packaging dimension: length  
Packaging dimension: width

Packaging dimension: height

Coverage features

Type of cover: Lockable cover

Cover locking: One-handed closure