

Staufix FKA auto. backwater valve DN 100, Floor slab, black



Article information

Item no.: 84100S GTIN: 4026092046371 Price group: 30

Advantages

- Safe, motor-driven closure system with optical probe
- Fast, simple and toolless maintenance
- Available as a complete set or module set

Description

The Premium automatic backwater valve for faecal and faecal-free wastewater is equipped with a motor-driven closure system which is closed automatically in the event of backwater. A second closure system serves as an emergency closure to be closed by hand. The station is controlled by a user-friendly control unit, which is optionally integrated in the building management system via a potential-free contact, or alarm and collective fault messages can be output via a GSM interface. Thanks to the modular KESSEL system, existing systems can easily be converted to a Pumpfix F backwater pumping station.

Variant

Emergency closure: yes

Protection class, probe: IP 68 (3m/48h)

Motor-driven backwater flaps: 1
Mechanical backwater flaps: 1

General characteristics

Colour: black
Standard: EN 13564
Nominal size (DN): 100
Outer diameter (OD): 110 mm
Type of wastewater: with sewage

Installation situation: floor slab installation

Delivery state: Pre-mounted for final assembly on site (sensor

system must be fitted on site and control unit must

be connected)

Backwater protection: Type 3
Motor type: KSM 140

Type de protection moteur: IP 68 (3m/48h)

Cable length: 5 m



Dimensions

Net weight: 18,2 kg Gross weight: 21 kg Groundwater resistant from lower edge of base 3000 mm

section:

750 mm Cutout dimension, width: Cutout dimension, length: 750 mm Vertical drop between inlet and outlet: 9 mm

Installation depth: 516 - 669 mm

Type of height adjustability: vertically adjustable upper section

Lenath: 642 mm Width: 590 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Socket version: including spigot and socket

Coverage features

Type of cover: Cover plate Cover material: Polymer Colour of cover: black Width of cover: 366 mm Length of cover: 366 mm Locking: Lock & Lift Load class: L 15 (EN 1253-1)

Tightness: surface water resistant

Control

Control unit: Comfort Alarm sensor: optical probe Level measurement instrument: optical probe optical Type of level measurement: Protection class control unit: IP 54 Mains frequency: 50 Hz 230 V Operating voltage: Length of mains cable for control unit: 1,4 m Potential-free contact: optional GSM interface: yes USB interface: yes Log book function: yes Multi-line display: yes Battery buffering: yes Self-diagnosis system (SDS): yes Connection to the BCS, BAC:

yes