


Yard drain System 400, DN 150, A, 580-710 mm



Article information

Item no.: 851151A
 GTIN: 4026092004371
 Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

Variant

System: 400
 Heating: without
 Contents of sludge trap: yes
 Waterproofing layer on the upper section: Connection flange
 Discharge rate (l/s) with 20 mm threshold: 4,5

General characteristics

Colour: black
 Standard: EN 752
 Nominal size (DN): 150
 Outer diameter (OD): 160 mm
 Odour trap: included

Dimensions

Vertical adjustment: 55 - 180 mm
 Net weight: 20 kg
 Gross weight: 20 kg
 Groundwater resistant from lower edge of base section: 500 mm
 Cutout dimension, width: 535 mm

Cutout dimension, length:	585 mm
Min. insertion depth:	55 mm
Adjustment range:	55 - 185
Installation depth:	580 - 710 mm
Type of height adjustability:	vertically adjustable upper section
Length:	563 mm
Width:	500 mm
Height:	580 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
 Tank/drain body	
Number of outlets:	1
Material of drain body:	Polymer
Socket version:	lateral
 Coverage features	
Type of cover:	Slotted cover
Cover material:	Polymer
Width of cover:	400 mm
Length of cover:	400 mm
Load class:	A 15 (EN 124)
Rim width:	400 mm
Rim length:	400 mm
Shape of upper section:	square
Contents of sludge trap:	yes