


## Yard drain System 400, DN 150, D, 580-710 mm



### Article information

Item no.: 851151D  
 GTIN: 4026092004395  
 Price group: 10

### Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

### Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

#### Variant

System:

400

Heating:

without

Contents of sludge trap:

yes

Waterproofing layer on the upper section:

Connection flange

Discharge rate (l/s) with 20 mm threshold:

4,5

#### General characteristics

Colour:

black

Standard:

EN 752

Nominal size (DN):

150

Outer diameter (OD):

160 mm

Odour trap:

included

#### Dimensions

Vertical adjustment:

55 - 180 mm

Net weight:

25,5 kg

Gross weight:

25,5 kg

Groundwater resistant from lower edge of base section:

500 mm

Cutout dimension, width:

535 mm

Cutout dimension, length:	585 mm
Min. insertion depth:	55 mm
Adjustment range:	55 - 185
Installation depth:	580 - 710 mm
Type of height adjustability:	vertically adjustable upper section
Length:	563 mm
Width:	500 mm
Height:	580 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
 Tank/drain body	
Number of outlets:	1
Material of drain body:	Polymer
Socket version:	lateral
 Coverage features	
Type of cover:	Round slotted cover
Cover material:	Grey iron
Width of cover:	450 mm
Length of cover:	450 mm
Load class:	D 400 (EN 124)
Rim width:	450 mm
Rim length:	450 mm
Shape of upper section:	square
Contents of sludge trap:	yes