

Yard drain System 400, DN 150, D, 730 - 1080 mm



Article information

Item no.: 851152D
 GTIN: 4026092004425
 Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

| | |
|--|---------|
| Variant | |
| System: | 400 |
| Heating: | without |
| Contents of sludge trap: | yes |
| Sealing water height: | 100 mm |
| Discharge rate (l/s) with 20 mm threshold: | 4,5 |

| | |
|-------------------------|----------|
| General characteristics | |
| Colour: | black |
| Standard: | EN 752 |
| Nominal size (DN): | 150 |
| Outer diameter (OD): | 160 mm |
| Odour trap: | included |

| | |
|--|-------------------------------------|
| Dimensions | |
| Net weight: | 50 kg |
| Gross weight: | 50 kg |
| Groundwater resistant from lower edge of base section: | 500 mm |
| Cutout dimension, width: | 535 mm |
| Cutout dimension, length: | 585 mm |
| Min. insertion depth: | 55 mm |
| Installation depth: | 730 - 1080 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

| | |
|--------------------------|---------------------|
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | Polymer |
| Socket version: | lateral |
| Coverage features | |
| Type of cover: | Round slotted cover |
| Cover material: | Grey iron |
| Colour of cover: | black |
| Width of cover: | 450 mm |
| Length of cover: | 450 mm |
| Surface: | EDM |
| Load class: | D 400 (EN 124) |
| Rim width: | 450 mm |
| Rim length: | 450 mm |
| Shape of upper section: | square |
| Contents of sludge trap: | yes |