

Yard drain System 400, DN 150, D, 730 - 1080 mm



Article information

Item no.: 851152D
 GTIN: 4026092004425
 Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

Variant

System:	400
Heating:	without
Contents of sludge trap:	yes
Sealing water height:	100 mm
Discharge rate (l/s) with 20 mm threshold:	4,5

General characteristics

Colour:	black
Standard:	EN 752
Nominal size (DN):	150
Outer diameter (OD):	160 mm
Odour trap:	included

Dimensions

Net weight:	50 kg
Gross weight:	50 kg
Groundwater resistant from lower edge of base section:	500 mm
Cutout dimension, width:	535 mm
Cutout dimension, length:	585 mm
Min. insertion depth:	55 mm
Installation depth:	730 - 1080 mm
Type of height adjustability:	vertically adjustable upper section
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body
Number of outlets: 1
Material of drain body: Polymer
Socket version: lateral

Coverage features
Type of cover: Round slotted cover
Cover material: Grey iron
Colour of cover: black
Width of cover: 450 mm
Length of cover: 450 mm
Surface: EDM
Load class: D 400 (EN 124)
Rim width: 450 mm
Rim length: 450 mm
Shape of upper section: square
Contents of sludge trap: yes