



## Controlfix backwater tech. mod. DN 125, closed channel passage







## **Article information**

Item no.: 851251

GTIN: 4026092079379

Price group: 60

## **Advantages**

- Komfort: expensive living or useful space is not lost
- No system noises or unpleasant odours and soiling in the building
- Straightforward installation thanks to low weight of the combined engineering chamber modules and variable upper sections for adaptation to the ground level

## **Description**

The backwater technical module is equipped with an integrated clean out Controlfix and access steps. Thanks to the modular KESSEL system, the clean out can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station.

Variant

Chamber system: modular chamber



General characteristics

Colour: black Material: PE-HD

Type of wastewater: with sewage

Installation situation: underground installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Approval: Z-42.1-527

**Dimensions** 

Net weight: 64 kg
Gross weight: 82 kg
Groundwater resistant from lower edge of base 3000 mm

section:

Vertical drop between inlet and outlet:

9 mm
Width:
1200 mm
Height:
520 mm
Packaging dimension:
length
Packaging dimension:
width
Packaging dimension:
height

Tank/drain body

Channel: continuous channel

Tank width max.: 1390 mm
Distance from centre of outlet pipe to tank 267 mm

ottom:

Distance from centre of inlet pipe to tank 277 mm

bottom:

Number of outlets: 1

Outlet nominal size (DN): 125 mm Inlet nominal size (DN): 125 mm

Number of inlets: 1

Clear width of tank (LW): 1000 mm