



Controlfix backwater tech. mod. DN 150, closed channel passage







Article information

Item no.: 851501

GTIN: 4026092079393

Price group: 60

Advantages

- Komfort: expensive living or useful space is not lost
- No system noises or unpleasant odours and soiling in the building
- Straightforward installation thanks to low weight of the combined engineering chamber modules and variable upper sections for adaptation to the ground level

Description

The backwater technical module is equipped with an integrated clean out Controlfix and access steps. Thanks to the modular KESSEL system, the clean out can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station.

Variant

Chamber system: modular chamber



General characteristics

Colour: black Material: PE-HD

Type of wastewater: with sewage

Installation situation: underground installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Approval: Z-42.1-527

Dimensions

Net weight: 64 kg
Gross weight: 82 kg
Groundwater resistant from lower edge of base 3000 mm

section:

Vertical drop between inlet and outlet:

9 mm
Width:
1200 mm
Height:
520 mm
Packaging dimension:
length
Packaging dimension:
width
Packaging dimension:
height

Tank/drain body

Channel: continuous channel

Tank width max.: 1390 mm
Distance from centre of outlet pipe to tank 267 mm

nottom:

Distance from centre of inlet pipe to tank 277 mm

bottom:

Number of outlets: 1

Outlet nominal size (DN): 150 mm Inlet nominal size (DN): 150 mm

Number of inlets: 1

Clear width of tank (LW): 1000 mm