

Chamber module LW 1000 floor slab Access LW 600, 380-629 mm, Class D



Article information

Item no.: 8740001 GTIN: 4026092065167 Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet installation is equipped with all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, a taper, upper section and cover.

General characteristics

Colour: black
Material: PE-HD
Standard: EN 13598-2

Installation situation: underground installation

Delivery state: Partly for on-site assembly (access steps have been

pre-mounted in the factory)

Approval: Z-42.1-527

Dimensions

Net weight:89 kgGross weight:105 kgGroundwater resistant from lower edge of base3000 mm

section:

Installation depth: 380 - 629 mm

Type of height adjustability: vertically adjustable upper section

Length: 1200 mm
Width: 1200 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height



Tank/drain body

Inlet max. scoring (DN): 150 mm
Clear width of tank (LW): 1000 mm
Clear width of entry (LW): 600 mm

Coverage features

Type of cover: Round cover plate

Cover material: Grey iron
Colour of cover: black
Width of cover: 659 mm
Height of cover: 122 mm
Length of cover: 659 mm
Surface: Grey iron
Locking: locked

Load class: D 400 (EN 124)

Tightness: surface water resistant