

Chamber module LW 1000 floor slab Access LW 600, 880-1129 mm, Class A/B



Article information

Item no.: 8740012 GTIN: 4026092065273

Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet installation is equipped with all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, a taper, upper section and cover.

General characteristics

Colour: black Material: PE-HD Standard: EN 13598-2

Installation situation: underground installation

Delivery state: Partly for on-site assembly (access steps have been

pre-mounted in the factory)

Z-42.1-527 Approval:

Dimensions

Net weight: 89,5 kg 106 kg Gross weight: Groundwater resistant from lower edge of base 3000 mm

section:

Installation depth: 880 - 1129 mm

Type of height adjustability: vertically adjustable upper section

1200 mm Length: Width: 1200 mm Packaging dimension: lenath Packaging dimension: width Packaging dimension: height



Tank/drain body

Inlet max. scoring (DN): 150 mm
Clear width of tank (LW): 1000 mm
Clear width of entry (LW): 600 mm

Coverage features

Type of cover: Round cover plate

Cover material: Grey iron Colour of cover: black Width of cover: 648 mm Height of cover: 95 mm Length of cover: 648 mm Surface: Grey iron unlocked Locking: Load class: B 125 (EN 124)

Tightness: surface water resistant